

Portable Cord -40°C + 90°C UL CSA MSHA Hard Usage - Medium Grade Mechanical Service



SPECIFICATIONS & STANDARDS

UL 62, CSA-C 22.2 No 49

CONSTRUCTION:

Conductors:	Flexible strand bare copper, ASTM B-174 and UL 62
Insulation:	EPR 90°C compound class 3 table 8 UL 62
Assembly:	Insulated conductors cabled together: integral filled jacket
Separator:	Paper tape or talc for 18-10 AWG
Jacket:	Black CPE compound class, 90°C + class 1.4, table 11, UL 62 integral fill
Color code:	ICEA S-58-679, Method 1, table 1, black, white, green

FEATURES	APPLICATION
<ul style="list-style-type: none"> - Excellent flexibility, resistance to oil, solvents, ozone, weather, sunlight and water - Flame test: meets VW-1, FT2, MSHA - Temperature range: -40°C to +90°C - Suitable for shallow water immersion 	<ul style="list-style-type: none"> - Industrial and processing equipment, cranes and hoists, track systems, tools, construction equipment, motors and associated machinery, garage portable lights, battery charger and equipment exposed to oils, solvents, flame, moisture and other electrical equipment

APPROVALS:

UL:	E123366 (CPE)
CSA:	1534535 (LL 103932) (CPE)
MSHA:	P-7K-254013 (CPE)

Part Number	Conductor Size	No. of Conductors	Power Conductor Stranding	Nominal Insulation Thickness		Nominal Jacket Thickness		Nominal O.D.		Approx. Weight	Ampacity (1) 30°C Ambient Temp.
				inches	mm	inches	mm	inches	mm		
SJ00W18-2 IF	18	2	16 / 30	0.030	0.76	0.030	0.76	0.28	7.2	42	10.0
SJ00W18-3 IF		3						0.30	7.7	52	10.0
SJ00W18-4 IF		4						0.33	8.4	63	7.0
SJ00W16-2 IF	16	2	26 / 30	0.030	0.76	0.030	0.76	0.31	7.9	53	13.0
SJ00W16-3 IF		3						0.33	8.4	66	13.0
SJ00W16-4 IF		4						0.36	9.1	83	10.0
SJ00W14-2 IF	14	2	41 / 30	0.030	0.76	0.030	0.76	0.34	8.7	68	18.0
SJ00W14-3 IF		3						0.36	9.2	88	18.0
SJ00W14-4 IF		4						0.40	10.1	110	15.0
SJ00W12-2 IF	12	2	65 / 30	0.030	0.76	0.045	1.14	0.41	10.4	104	25.0
SJ00W12-3 IF		3						0.43	10.9	131	25.0
SJ00W12-4 IF		4						0.47	11.9	163	20.0
SJ00W10-2 IF	10	2	103 / 30	0.045	1.14	0.060	1.52	0.54	13.8	177	30.0
SJ00W10-3 IF		3						0.58	14.6	225	30.0
SJ00W10-4 IF		4						0.63	16.0	279	25.0

(1) Ampacity – Free air measured; Based on continuous duty at 90°C conductor temperature

STANDARD PRINT LEGEND:

TF CABLE FLEXTREME (COND) (SIZE) (mm²) (UL) TYPE SJ00W E123366 90C SUN & WATER RES 300V CSA TYPE SJ00W 90C LL 103932 FT2 -40C P-7K-254013 MSHA

SPECIAL FACTORY OPTIONS:

Color jacket: Yellow, Orange