



Grounding Cable

600V

ASTFM F855 type I; ASTM B-172

Grounding cables with flexible copper conductor Synthetic CPE compound

APPLICATIONS

A grounding flexible cable used for grounding jumpers installed temporarily for protective grounding of de-energized circuits

CONSTRUCTION

Conductor	Annealed bare copper stranded wires ASTM B-172 class K
Separator	Polyester tape applied longitudinally over conductor
Jacket:	Flame retardant, oil resistant, synthetic thermosetting CPE compound
Colour of jacket:	Yellow



Features

Excellent flexibility, Flame retardant. Temperature range: -40°C to +90°C.
Spark tested 12,5kV - C22.2 No. 96-09. Minimum bending radius: 6 x D ; D – overall diameter of cable

Technical and Electrical Characteristic

Part Number	Nominal cross-sectional area of conductor	Number of wires in conductor x Diameter	Nominal thickness of jacket		Overall diameter		Approximate weight	
			Inches	mm	Inches	mm	kg/km	LBS/1000ft
GRDCPE-YEL2/0-1	2/0	1323x0,254	0,105	2,7	0,693	17,6	795	534
GRDCPE-YEL4/0-1	4/0	2107x0,254	0,110	2,8	0,843	21,4	1215	816

Standard print legend:

TF CABLE (SIZE) 600V GROUNDING CABLE mfg. acc to ASTM F855 type I

All the information in this document – including tables and diagrams – is given in good faith and believed to be correct at the time of publication. The information does not constitute a warranty nor representation for which TELE-FONIKA Kable assumes legal responsibility. TELE-FONIKA Kable reserves rights to introduce changes to the document at any time