

MP-GC 8000V EPR/CPE

Mine Power Feeder Cable Extra Heavy Duty EPR / CPE 90°C MSHA Mining Grade



SPECIFICATIONS & STANDARDS

ICEA S-75-381/NEMA WC58, ASTM B 8

CONSTRUCTION:

- Conductor:** Bare copper, concentric strand ASTM B 8
- Conductor shield:** Semi-conducting tape and compound, ICEA S-75-381 sec 3.14
- Insulation:** Ethylene-propylene rubber (EPR), ICEA S-75-381, table 4-3/4-4
- Insulation shield:** Semi-conducting compound, ICEA S-75-381 and 0.005 copper tape
- Grounding cond:** Tin copper Class B, ICEA S-75-381, table 4-1
- Ground check:** Bare copper, ICEA S-75-381 table 4-1; insulation color: yellow
- Assembly:** Three power conductor, ground check and two non-insulated grounding conductors cabled with rubber fillers to make a round core; Single faced rubber filled binder tape applied overall
- Jacket:** Black extra heavy duty CPE thermoset compound, ICEA S-75-381, table 3-3, 3-22, sec. 3.21
- Color code:** Color code tape: black, white, red applied under metallic shielding tape provides circuit identification, ICEA S-75-381 sec 4.6

FEATURES	APPLICATION
<ul style="list-style-type: none"> - Ozone, sun, weather and flame resistant - Oil and heat resistant - Maximum continuous conductor temperature 90°C - Indent printed for easy identification 	<ul style="list-style-type: none"> - For high-voltage power distribution when installed in ducts, conduits, open air and for direct burial in wet and dry locations. - For semi-permanent and permanent installations in tunnels, shafts and bore holes. - Other industrial and mining applications requiring shielding.

APPROVALS:

MSHA: P-07-KA050003-1

SPECIAL FACTORY OPTIONS:

Jacket: Other colors available
Neoprene®

UL TYPE MP-GC – 8000 VOLTS – 100% INSULATION LEVEL

Part Number	Power Conductor Size	Power Conductor Stranding	Size		Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal O.D.		Approx. Weight	
			Ground	Ground Check			inches	mm	lbs/1000 ft	kgs/km
	AWG or MCM	No. of Stranding	AWG	AWG	inches	inches	inches	mm	lbs/1000 ft	kgs/km
MPGC8KV4-3-CPE	4 AWG	7	8	8	0.115	0.110	1.43	36.3	1410	2042
MPGC8KV2-3-CPE	2 AWG	7	6	8	0.115	0.110	1.55	39.4	1750	2604
MPGC8KV1-3-CPE	1 AWG	19	5	8	0.115	0.110	1.65	41.9	2050	3051
MPGC8KV1/0-3-CPE	1/0 AWG	19	4	8	0.115	0.140	1.75	44.5	2410	3587
MPGC8KV2/0-3-CPE	2/0 AWG	19	3	8	0.115	0.140	1.88	47.8	2900	4316
MPGC8KV4/0-3-CPE	4/0 AWG	19	1	8	0.115	0.140	2.12	53.8	4100	6102
MPGC8KV250-3-CPE	250 MCM	37	1/0	8	0.115	0.140	2.25	57.2	4720	7024
MPGC8KV350-3-CPE	350 MCM	37	2/0	8	0.115	0.140	2.46	62.5	6070	9030
MPGC8KV500-3-CPE	500 MCM	37	4/0	8	0.115	0.140	2.75	69.9	8350	12400

ELECTRICAL AND MECHANICAL PARAMETERS

Power-Grounding Conductor Size	Power Conductor Resistance at 20°C	Grounding Conductor Resistance at 20°C	Ground Check Conductor Resistance at 20°C	Inductance per length unit	Operating Capacitance per length unit	Permissible short-circuit Current ⁽²⁾ (1s)	Ampacity ⁽¹⁾ 40°C Ambient Temp.	Maximum Permissible Tension Force
AWG or MCM	Ω/1000Ft	Ω/1000Ft	Ω/1000Ft	mH/1000Ft	μF/1000Ft	kA	A	N
4 AWG – 8 AWG	0.258	0.678	0.652	0.117	0.09	3.03	122	1270
2 AWG – 6 AWG	0.162	0.427	0.652	0.111	0.10	4.80	159	1600
1 AWG – 5 AWG	0.129	0.338	0.652	0.107	0.11	6.06	184	2500
1/0 AWG – 4 AWG	0.102	0.269	0.652	0.104	0.12	7.65	211	3200
2/0 AWG – 3 AWG	0.081	0.213	0.652	0.098	0.14	9.64	243	4000
4/0 AWG – 1 AWG	0.051	0.134	0.652	0.093	0.16	15.30	321	6400
250 MCM – 1/0 AWG	0.043	0.106	0.652	0.087	0.20	18.16	355	7700
350 MCM – 2/0 AWG	0.031	0.081	0.652	0.083	0.22	25.31	435	9100
500 MCM – 4/0 AWG	0.022	0.051	0.652	0.080	0.26	36.18	536	15100

(1) Ampacity- Free air measured; Based on continuous duty at 90°C conductor temperature (2) Short-circuit current (1s) – Based on conductor temperature from 90°C up to 250°C

STANDARD PRINT LEGEND:

TF CABLE 8000V (SIZE) GROUNDED MP-GC P-07-KA050003-1-MSHA



555 Remington Blvd, Bolingbrook, IL 60440 | tel: 630-406-9000 fax: 630-406-6574
e-mail: sales@tfcable.com | http://www.tfcable.com