


# TYPE SH 25000V

## Single Conductor Medium Voltage Portable Power Cable



### SPECIFICATIONS & STANDARDS

According to ICEA S-75-381/NEMA WC-58, ASTM B172, ASTM B 33

### CONSTRUCTION:

- Conductors:** Annealed flexible stranded tin coated copper Class I in accordance with ASTM B-172 and ICEA S-75-381
- Conductor shielding:** Semi-conducting tape+ layer over the conductor
- Insulation:** Ethylene-propylene rubber (EPR)
- Insulation shield:** Semi-conducting tape +Composite tinned copper/nylon braid. Covering minimum 60% Cable consist of EPR insulated central conductor with helically applied copper drain wire shield conductors over the insulation semi-conductive tape shield. Reinforcing tape over insulation shield
- Jacket:** Heavy duty thermosetting poly-chloroprene jacket
- Colour of jacket:** Black
- Minimum bending radius:** Eight x overall diameter of the cable

Standard length cable packing: 1000 ft on drums. Other forms of packing and delivery are available on request.

FEATURES	APPLICATION
<ul style="list-style-type: none"> <li>- Excellent flexibility</li> <li>- Highly ozone, sun, weather and flame resistant</li> <li>- Rated and flexible at -40°C</li> <li>- Excellent impact and abrasion resistant</li> <li>- Oil and heat resistant</li> </ul>	<ul style="list-style-type: none"> <li>- These cables are designed for use on mobile substation equipment</li> <li>- Other industrial application</li> </ul>

Part Number	Power Conductor Size	Conductor Stranding	Nominal Insulation Thickness	Nominal Jacket Thickness	Approx. Overall Diameter	Approx. Weight		Ampacity (1) 40°C Ambient Temp.
	AWG / MCM		inches	inches	inches	lbs/1000 ft	kgs/km	A
SH25KV-2	2AWG-1	259x0.0157	0.295	0.170	1.358	1090	1622	195
SH25KV-1	1AWG-1	259x0.0177		0.170	1.425	1216	1810	222
SH25KV-1/0	1/0AWG-1	266x0.0197		0.170	1.468	1333	1984	255
SH25KV-2/0	2/0AWG-1	342x0.0193		0.170	1.516	1474	2193	293
SH25KV-3/0	3/0AWG-1	418x0.0197		0.170	1.583	1652	2459	337
SH25KV-4/0	4/0AWG-1	532x0.0197		0.190	1.661	1890	2813	389
SH25KV-250	250MCM-1	627x0.0197		0.190	1.744	2095	3118	430
SH25KV-300	300MCM-1	740x0.0197		0.190	1.807	2299	3421	480
SH25KV-350	350MCM-1	888x0.0193		0.190	1.850	2519	3749	529
SH25KV-500	500MCM-1	1221x0.0197		0.205	2.008	3143	4677	659

### STANDARD PRINT LEGEND:

TF CABLE (25000V) (SIZE) TYPE SH OIL RESISTANT -40°C +90°C

