


TYPE SH 35000V

Single Conductor Medium Voltage Portable Power Cable



SPECIFICATIONS & STANDARDS

According to ICEA S-75-381/NEMA WC-58, ASTM B172, ASTM B 33

CONSTRUCTION:

- Conductors:** Annealed flexible stranded tin coated copper Class I in accordance with ASTM B-172 and ICEA S-75-381
- Conductor shielding:** Semi-conducting tape+ layer over the conductor
- Insulation:** Ethylene-propylene rubber (EPR)
- Insulation shield:** Semi-conducting tape +Composite tinned copper/nylon braid. Covering minimum 60% Cable consist of EPR insulated central conductor with helically applied copper drain wire shield conductors over the insulation semi-conductive tape shield. Reinforcing tape over insulation shield
- Jacket:** Heavy duty thermosetting poly-chloroprene jacket
- Colour of jacket:** Black
- Minimum bending radius:** Eight x overall diameter of the cable

Standard length cable packing: 1000 ft on drums. Other forms of packing and delivery are available on request.

FEATURES	APPLICATION
<ul style="list-style-type: none"> - Excellent flexibility - Highly ozone, sun, weather and flame resistant - Rated and flexible at -40°C - Excellent impact and abrasion resistant - Oil and heat resistant 	<ul style="list-style-type: none"> - These cables are designed for use on mobile substation equipment - Other industrial application

Part Number	Power Conductor Size	Conductor Stranding	Nominal Insulation Thickness	Nominal Jacket Thickness	Approx. Overall Diameter	Approx. Weight		Ampacity (1) 40°C Ambient Temp.
	AWG / MCM		inches	inches		lbs/1000 ft	kgs/km	
SH35KV-2	2AWG-1	259x0.0157	0.345	0.190	1.500	1288	1916	195
SH35KV-1	1AWG-1	259x0.0177		0.190	1.551	1401	2085	222
SH35KV-1/0	1/0AWG-1	266x0.0197		0.190	1.595	1523	2266	255
SH35KV-2/0	2/0AWG-1	342x0.0193		0.190	1.626	1644	2446	293
SH35KV-3/0	3/0AWG-1	418x0.0197		0.205	1.724	1881	2799	337
SH35KV-4/0	4/0AWG-1	532x0.0197		0.205	1.772	2555	3082	389
SH35KV-250	250MCM-1	627x0.0197		0.205	1.854	2286	3402	430
SH35KV-300	300MCM-1	740x0.0197		0.205	1.917	2495	3714	480
SH35KV-350	350MCM-1	888x0.0193		0.220	1.988	2781	4137	529
SH35KV-500	500MCM-1	1221x0.0197		0.220	2.138	3406	5068	659

STANDARD PRINT LEGEND:

TF CABLE (35000V) (SIZE) TYPE SH OIL RESISTANT -40°C +90°C



TELE-FONIKA CABLE AMERICAS

555 Remington Blvd, Bolingbrook, IL 60440 | tel: 630-406-9000 fax: 630-406-6574
e-mail: sales@tfcable.com | http://www.tfcable.com

07/12 v2.8