



SHD-GC

15kV

ICEA S-75-381/NEMA WC-58

Round portable power cable Mining grade

APPLICATIONS

Use on AC off track equipment such as long wall miners loaders, drills, shovels, conveyors, pumps and mobile equipment requiring grounding conductors and a ground check conductor and metallic shielding overall. Other industrial, mining applications

CONSTRUCTION

Conductors	Soft drawn flexible stranded tinned copper wires
Conductor shield	Semi-conducting layer over the conductor
Insulation	Ethylene-propylene rubber (EPR)
Insulation shield	Semi-conducting tape + composite tinned copper/polyamide braid. Covering minimum 60%.
Circuit identification	The polyamide in the shielding braid is colored black, white, red
Grounding	Soft drawn flexible stranded tinned copper wires
Ground check	Yellow PP insulated soft drawn flexible stranded tinned copper wires
Assembly	Three power, ground check and two non-insulated grounding conductors cabled together to form a round cable core
Separator	A single faced rubber filled binder tape applied over core
Outer jacket	Extra heavy duty, high torsion resistant, integral-filled, reinforced poly-chloroprene (CR) thermosetting jacket
Color of outer jacket	Black
Minimum bending radius	Eight times overall diameter of the cable



Features

Excellent flexibility. Highly ozone, sun, weather and flame resistant. Rated and flexible at -40°C. Excellent impact and abrasion resistant. Oil and heat resistant. Indent printed for easy identification.

Approvals

MSHA: P-07-KA060012

Selection Data

Part Number	Cond. Size	Cond. Strand	Cond. Size		Nominal Insulation Thickness		Nominal Jacket Thickness		Outside Diameter		Approx. Weight		Max. Tensile Force
	AWG/MCM	No. of wires	AWG	GC	Inches	mm	Inches	mm	Inches	mm	Lbs./1000ft.	kg/km	
SHDGC15KV2-3	2	259	6	8	0.210	5.33	0.235	5.97	2.31	58.8	3264	4857	1500
SHDGC15KV1-3	1	259	5	8	0.210	5.33	0.235	5.97	2.42	61.4	3644	5423	1900
SHDGC15KV1/0-3	1/0	266	4	8	0.210	5.33	0.250	6.35	2.53	64.3	4110	6116	2400
SHDGC15KV2/0-3	2/0	342	3	8	0.210	5.33	0.250	6.35	2.62	66.5	4625	6883	3000
SHDGC15KV3/0-3	3/0	418	2	8	0.210	5.33	0.265	6.73	2.78	70.6	5332	7935	3800
SHDGC15KV4/0-3	4/0	532	1	8	0.210	5.33	0.265	6.73	2.92	74.2	6141	9138	4800
SHDGC15KV250-3	250*	627	1/0	8	0.210	5.33	0.265	6.73	2.97	75.5	7082	10539	5800
SHDGC15KV350-3	350*	888	2/0	8	0.210	5.33	0.280	7.11	3.26	82.7	8364	12447	7900

* Based on ICEA S-75-381 NEMA WC 58

Electrical parameters

Power-Grounding Conductor Size	Power Conductor Resistance at 25°C	Grounding Conductor Resistance at 25°C	Ground-check Conductor Resistance at 25°C	Inductance per unit length	Operating Capacitance per unit length	Permissible short-circuit Current (1s) (2)	Ampacity(1) 40°C Ambient Temp
AWG or MCM	Ω/1000Ft	Ω/1000Ft	Ω/1000Ft	mH/1000Ft	µF/1000Ft	kA	A
2 AWG	0,172	0,436	0,679	0,131	0,07	4,80	164
1 AWG	0,137	0,346	0,679	0,126	0,07	6,06	187
1/0 AWG	0,109	0,274	0,679	0,122	0,08	7,65	215
2/0 AWG	0,0868	0,217	0,679	0,115	0,09	9,64	246
3/0 AWG	0,0688	0,172	0,679	0,114	0,09	12,15	283
4/0 AWG	0,0546	0,137	0,679	0,109	0,10	15,30	325
250 MCM	0,0466	0,109	0,679	0,101	0,12	18,16	359
350 MCM	0,0333	0,0868	0,679	0,096	0,13	25,31	438

(1) Ampacity –Based on continuous duty at 90°C conductor temperature

(2) Short-circuit current (1s) – Based on conductor temperature from 90°C up to 250°C

Standard print legend:

TF CABLE 15000V 3/C (SIZE) TYPE SHD-GC FT1 FT5 (-40C) +90C P-07-KA060012-MSHA

Special factory option

Jacket: Other colors available

Jacket: TPU jacket available

MSHA: P-07-KA120001 (TPU)

All the information in this document – including tables and diagrams – is given in good faith and believed to be correct at the time of publication. The information does not constitute a warranty nor representation for which TELE-FONIKA Kable assumes legal responsibility. TELE-FONIKA Kable reserves rights to introduce changes to the document at any time