



# SHD-GC

## 8kV



CSA C22.2 No. 96-13

Round portable power cable Mining grade

### APPLICATIONS

Use on AC off track equipment such as long wall miners loaders, drills, shovels, conveyors, pumps and mobile. equipment requiring grounding conductors and a ground check conductor and metallic shielding overall. Other industrial, mining applications

### CONSTRUCTION

Conductors	Soft drawn flexible stranded tinned copper wires
Conductor shield	Semi-conducting layer over the conductor
Insulation	Ethylene-propylene rubber (EPR)
Insulation shield	Semi-conducting tape + composite tinned copper/polyamide braid. Covering minimum 60%
Circuit identification	The polyamide in the shielding braid is colored black, blue, red
Grounding	Soft drawn flexible stranded tinned copper wires
Ground check	Yellow PP insulated soft drawn flexible stranded tinned copper wires
Assembly	Three power, ground check and two non-insulated grounding conductors cabled together to form a round cable core
Separator	A single faced rubber filled binder tape applied over core
Outer jacket	Extra heavy duty, high torsion resistant, integral-filled, reinforced poly-chloroprene (CR) thermosetting jacket
Color of outer jacket	Black
Minimum bending radius	Eight times overall diameter of the cable



### Features

Excellent flexibility. Highly ozone, sun, weather and flame resistant. Rated and flexible at -40°C. Excellent impact and abrasion resistant. Oil and heat resistant. Indent printed for easy identification.

### Approvals

CSA: 1523058 (LR 103932), FT 1, FT-5, MSHA: P-07-KA060012

## Selection Data

Part Number	Cond. Size	Cond. Strand	Cond. Size		Nominal Insulation Thickness		Nominal Jacket Thickness		Outside Diameter		Approx. Weight		Max. Tensile Force	
	AWG/ MCM	No. of wires	AWG	GRD	GC	Inches	mm	Inches	mm	Inches	mm	Lbs./ 1000ft.	kg/km	N
SHDGC8KV4-3CSA	4	259 7x37	9		8	0.150	3.81	0.205	5.21	1.86	47.2	2099	3123	950
SHDGC8KV2-3CSA	2	259 7x37	7		8	0.150	3.81	0.220	5.59	2.00	50.9	2603	3874	1500
SHDGC8KV1-3CSA	1	259 7x37	6		8	0.150	3.81	0.220	5.59	2.12	53.9	2967	4415	1900
SHDGC8KV1/0-3CSA	1/0	266 19x14	5		8	0.150	3.81	0.220	5.59	2.19	55.7	3316	4934	2400
SHDGC8KV2/0-3CSA	2/0	342 19x18	4		8	0.150	3.81	0.235	5.97	2.35	59.8	3958	5890	3000
SHDGC8KV3/0-3CSA	3/0	418 19x22	3		8	0.150	3.81	0.250	6.35	2.49	63.2	4541	6757	3800
SHDGC8KV4/0-3CSA	4/0	532 19x18	2		8	0.150	3.81	0.250	6.35	2.61	66.4	5270	7843	4800
SHDGC8KV250-3CSA	250	627 19x33	1		8	0.150	3.81	0.250	6.35	2.78	70.5	6096	9071	5800
SHDGC8KV350-3CSA	350	888 37x24	1/0		8	0.150	3.81	0.280	7.11	3.06	77.8	7801	11609	7900
SHDGC8KV500-3CSA	500	1221 37x33	3/0		8	0.150	3.81	0.295	7.49	3.39	86.2	9940	14792	11400

## Electrical parameters

Power-Grounding Conductor Size	Power Conductor Resistance at 25°C	Grounding Conductor Resistance at 25°C	Ground-check Conductor Resistance at 25°C	Inductance per unit length	Operating Capacitance per unit length	Permissible short-circuit Current (1s) (2)	Ampacity(1) 40°C Ambient Temp
AWG or MCM	Ω/1000Ft	Ω/1000Ft	Ω/1000Ft	mH/1000Ft	µF/1000Ft	kA	A
4 AWG	0,274	0,857	0,679	0,119	0,09	3,03	122
2 AWG	0,172	0,539	0,679	0,112	0,10	4,80	159
1 AWG	0,137	0,436	0,679	0,108	0,11	6,06	184
1/0 AWG	0,109	0,346	0,679	0,105	0,12	7,65	211
2/0 AWG	0,0868	0,274	0,679	0,099	0,14	9,64	243
3/0 AWG	0,0688	0,217	0,679	0,098	0,14	12,15	279
4/0 AWG	0,0546	0,172	0,679	0,094	0,16	15,30	321
250 MCM	0,0466	0,137	0,679	0,089	0,18	18,16	355
350 MCM	0,0333	0,109	0,679	0,085	0,21	25,31	435
500 MCM	0,0233	0,0688	0,679	0,082	0,24	36,18	536

(1) Ampacity –Based on continuous duty at 90°C conductor temperature

(2) Short-circuit current (1s) – Based on conductor temperature from 90°C up to 250°C

### Standard print legend:

TF CABLE 8000V 3/C (SIZE) TYPE SHD-GC CSA LR 103932 FT1  
FT5 (-40C) +90C P-07-KA060012-MSHA

### Special factory option

Jacket: Other colors available

Jacket: TPU jacket available

MSHA: P-07-KA120001 (TPU)