

TYPE G-GC 3/c 600 / 2kV

Three conductor Flat portable power cable Mining grade

SPECIFICATIONS & STANDARDS

ICEA S-75-381/NEMA WC58, ICEA S-95-658/NEMA WC70
ASTM B 172, ASTM B 33

CONSTRUCTION:

Conductors:	Annealed flexible stranded tin coated copper in accordance with ASTM B 172 and ICEA S-75-381; Conductors D-shaped and rectangle cross section
Separator:	A suitable tape separator between the conductor and insulation
Insulation:	Ethylene-propylene rubber (EPR) type EP, 90°C
Circuit identification:	Color coding of power conductors shall be black, white, red in accordance with Par. 3.18 of ICEA S-75-381
Reinforcement:	Nylon open braid over assembly
Jacket:	CPE thermosetting compound, extra heavy duty in accordance with par. 3.21 of ICEA S-75-381; Optional Neoprene® jacket available
Color of jacket:	Black; Other colors available



FEATURES	APPLICATION
<ul style="list-style-type: none">- Excellent flexibility- Water resistant and flame retardant- Rated and flexible at -40°C- Excellent impact and abrasion resistant- Ozone sunlight oil, grease, weather, chemical resistant- Indent printed for easy identification	<ul style="list-style-type: none">- For use on A.C. off-track mining equipment- Especially designed for A.C. shuttle car service

Standard length cable packing: 1000 ft reels; Other forms of packaging available

APPROVALS:

MSHA: P-7K-268108

Neoprene is a registered trademark of DuPont



TELE-FONIKA CABLE AMERICAS

1160 Pierson Drive, Suite 102
Batavia, IL 60510
tel: 630-406-9000 fax: 630-406-6574

12/08 v2.4

TYPE G-GC 3/c 600 / 2kV

Part Number	Power Conductor Size	Power Conductor Stranding	Size		Nominal Insulation Thickness	Nominal O.D.		Approx. Weight		Ampacity (1) 40°C Ambient Temp.
			Ground	Ground Check		inches	mm	lbs/1000 ft	kgs/km	
	AWG	No. of Stranding	AWG	AWG	inches	inches	mm	lbs/1000 ft	kgs/km	A
GGC6-3 Flat Mining	6 AWG	133 7x19	8	8	0.06	0.67x1.69	17.0x42.9	939	1397	79
GGC4-3 Flat Mining	4 AWG	259 7x37	7	8	0.06	0.75x1.89	19.1x48.0	1250	1860	104
GGC2-3 Flat Mining	2 AWG	259 7x37	5	8	0.06	0.81x2.23	20.6x56.6	1701	2531	138
GGC1-3 Flat Mining	1 AWG	259 7x37	4	8	0.08	0.97x2.48	24.6x63.0	2180	3244	161
GGC1/0-3 Flat Mining	1/0 AWG	259 7x37	3	8	0.08	1.01x2.67	25.7x67.8	2560	3810	186
GGC2/0-3 Flat Mining	2/0 AWG	329 7x47	2	8	0.08	1.10x2.86	27.9x72.6	3050	4539	215
GGC3/0-3 Flat Mining	3/0 AWG	418 19x22	1	8	0.08	1.18x3.12	29.9x79.2	3494	5200	249
GGC4/0-3 Flat Mining	4/0 AWG	532 19x28	1/0	8	0.08	1.24x3.30	31.5x83.8	4260	6340	287

(1) Ampacity – Free air measured; Based on continuous duty at 90°C conductor temperature

STANDARD PRINT LEGEND:

TELE-FONIKA (SIZE) TYPE G-GC PORTABLE POWER CABLE 600 / 2000V 90C SUN OIL RES 90C WET OR DRY P-7K-268108-MSHA

