

Portable Power Cable Extra Heavy Duty EPR / NEO 90°C MSHA Mining Grade



SPECIFICATIONS & STANDARDS

ICEA S-75-381/NEMA WC58, ASTM B 172, ASTM B 33

CONSTRUCTION:

- Conductors:** Flexible strand tinned copper conductor, ASTM B-172 and ICEA S-75-381, table 3-22
- Separator:** Polyester tape between conductor and insulation. ICEA S-75-381
- Conductor Shield:** Extruded semi-conducting layer over conductor. ICEA S-75-381 sec. 3.14
- Insulation:** Ethylene-propylene rubber (EPR) ICEA S-75-381, table 3-22
- Insulation Shield:** Semi-conducting bedding tape and composite tinned copper/polyamide braid 60% minimum coverage
- Color Code:** Polyamide braid color code - black, white, red, ICEA S-75-381
- Grounding Cond:** Tinned copper - ICEA S-75-381 Tab. 3-22
- Ground Check:** Yellow polypropylene-insulated tinned copper conductor, ICEA S-75-381 Tab. 3-22
- Cable Assembly:** Three power conductors, ground check and two non-insulated grounding conductors cabled together to form a round cable core
- Separator:** Single faced rubber-filled binder tape applied over core
- Jacket:** Black, extra heavy duty, high torsion-resistant, integral-filled, reinforced Neoprene thermoset jacket, ICEA S-75-381 Tab. 3-3, 3-22, Sec. 3.21

FEATURES	APPLICATION
<ul style="list-style-type: none"> - Excellent flexibility - Highly ozone, sun, weather, water and flame resistant - Rated and flexible at -50°C - Excellent impact and abrasion resistant - Oil and heat resistant - Indent printed for easy identification 	<ul style="list-style-type: none"> - Use on AC off track equipment such as longwall miners loaders, drills, conveyors, pumps and mobile equipment requiring grounding conductors and a ground check conductor and metallic shielding overall - Maximum continuous conductor temperature is 90°C

APPROVALS:

MSHA: P-07-KA060012-1

Part Number	Power Conductor Size	Power Conductor Stranding	Ground Check Conductor Size	Grounding Conductor		Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal O.D.		Approx. Weight	
				Size	Stranding			inches	mm	lbs/1000 ft	kgs/km
SHDGC8KV1/0-3	1/0 AWG	266 19x14	8	4	259 7x37	0.150	0.220	2.32	58.9	3530	5112
SHDGC8KV2/0-3	2/0 AWG	342 19x18		3	259 7x37	0.150	0.235	2.46	62.5	4160	6191
SHDGC8KV4/0-3	4/0 AWG	532 19x28		1	259 7x37	0.150	0.250	2.75	69.9	5590	8319
SHDGC15KV2-3	2 AWG	259 7x37	8	6	133 7x19	0.210	0.235	2.41	61.2	3505	5216
SHDGC15KV1/0-3	1/0 AWG	266 19x14		4	259 7x37	0.210	0.250	2.64	67.1	4614	6867
SHDGC15KV2/0-3	2/0 AWG	342 19x18		3	259 7x37	0.210	0.250	2.73	69.3	4895	7285
SHDGC15KV4/0-3	4/0 AWG	532 19x28		1	259 7x37	0.210	0.265	3.05	77.5	6821	10151

ELECTRICAL AND MECHANICAL PARAMETERS

Power-Grounding Conductor Size	Power Conductor Resistance at 25°C	Grounding Conductor Resistance at 25°C	Ground Check Conductor Resistance at 25°C	Inductance per unit length	Operating Capacitance per unit length	Permissible Short-Circuit Current ⁽²⁾ (1s)	Ampacity ⁽¹⁾ 40°C Ambient Temp.	Maximum Permissible Tensile Force
AWG or MCM	Ω/1000Ft	Ω/1000Ft	Ω/1000Ft	mH/1000Ft	μF/1000Ft	kA	A	N
2 AWG – 6 AWG	0.172	0.436	0.679	0.122	0.09	4.80	159	1500
1/0 AWG – 4 AWG	0.109	0.274		0.113	0.10	7.65	211	2400
2/0 AWG – 3 AWG	0.0868	0.227		0.107	0.11	9.64	243	3000
4/0 AWG – 1 AWG	0.0546	0.137		0.101	0.13	15.30	321	4800

(1) Ampacity- Free air measured; Based on continuous duty at 90°C conductor temperature (2) Short-circuit current (1s) – Based on conductor temperature from 90°C up to 250°C

STANDARD PRINT LEGEND:

TF CABLE (VOLTAGE) (SIZE) TYPE SHD-GC
FT1 FT5 (-50C) +90C P-07-KA060012-MSHA

SPECIAL FACTORY OPTIONS:

- Jacket:** Red, yellow, green, orange, blue
- MSHA:** P-7K-268101 (CPE)
- Jacket:** TPU Red, yellow, green, orange, blue
- MSHA:** P-07-KA030001 (TPU)