

SHD-GC 8000V

Portable Power Cable Extra Heavy Duty EPR / NEO 90°C MSHA Mining Grade



SPECIFICATIONS & STANDARDS

ICEA S-75-381/NEMA WC58, ASTM B 172, ASTM B 33

CONSTRUCTION:

- Conductors:** Flexible strand tinned copper conductor, ASTM B-172 and ICEA S-75-381, table 3-22
- Separator:** Polyester tape between conductor and insulation. ICEA S-75-381
- Conductor Shield:** Extruded semi-conducting layer over conductor. ICEA S-75-381 sec. 3.14
- Insulation:** Ethylene-propylene rubber (EPR) ICEA S-75-381, table 3-22
- Insulation Shield:** Semi-conducting bedding tape and composite tinned copper/polyamide braid 60% minimum coverage
- Color Code:** Polyamide braid color code - black, white, red, ICEA S-75-381
- Grounding Cond:** Tinned copper - ICEA S-75-381 Tab. 3-22
- Ground Check:** Yellow polypropylene-insulated tinned copper conductor, ICEA S-75-381 Tab. 3-22
- Cable Assembly:** Three power conductors, ground check and two non-insulated grounding conductors cabled together to form a round cable core
- Separator:** Single faced rubber-filled binder tape applied over core
- Jacket:** Black, extra heavy duty, high torsion-resistant, integral-filled, reinforced Neoprene thermoset jacket, ICEA S-75-381 Tab. 3-3, 3-22, Sec. 3.21

FEATURES	APPLICATION
<ul style="list-style-type: none"> - Excellent flexibility - Highly ozone, sun, weather, water and flame resistant - Rated and flexible at -50°C - Excellent impact and abrasion resistant - Oil and heat resistant - Indent printed for easy identification 	<ul style="list-style-type: none"> - Use on AC off track equipment such as longwall miners loaders, drills, conveyors, pumps and mobile equipment requiring grounding conductors and a ground check conductor and metallic shielding overall - Maximum continuous conductor temperature is 90°C

APPROVALS:

MSHA: P-07-KA060012

SPECIAL FACTORY OPTIONS:

- Jacket:** Red, yellow, green, orange, blue
- MSHA:** P-7K-268101 (CPE)
- Jacket:** TPU Red, yellow, green, orange, blue
- MSHA:** P-07-KA030001 (TPU)

Part Number	Power Conductor Size	Power Conductor Stranding	Ground Check Conductor Size	Grounding Conductor		Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal O.D.		Approx. Weight	
				Size	Stranding			inches	mm	lbs/1000 ft	kgs/km
SHDGC8KV4-3	4 AWG	259 7x37	8	8	133 7x19	0.150	0.205	1.94	49.3	2132	3173
SHDGC8KV2-3	2 AWG	259 7x37	8	6	133 7x19	0.150	0.220	2.12	53.8	2780	4137
SHDGC8KV1-3	1 AWG	259 7x37	8	5	133 7x19	0.150	0.220	2.21	56.0	3300	4911
SHDGC8KV1/0-3	1/0 AWG	266 19x14	8	4	259 7x37	0.150	0.220	2.32	58.9	3530	5112
SHDGC8KV2/0-3	2/0 AWG	342 19x18	8	3	259 7x37	0.150	0.235	2.46	62.5	4160	6191
SHDGC8KV3/0-3	3/0 AWG	418 19x22	8	2	259 7x37	0.150	0.250	2.62	66.6	5000	7440
SHDGC8KV4/0-3	4/0 AWG	532 19x28	8	1	259 7x37	0.150	0.250	2.75	69.9	5590	8319
SHDGC8KV250-3	250 MCM	627 19x33	8	1/0	266 19x14	0.150	0.250	2.89	73.4	6680	9941
SHDGC8KV350-3	350 MCM	888 37x24	8	2/0	342 19x18	0.150	0.280	3.20	81.3	8410	12515
SHDGC8KV500-3	500 MCM	1221 37x33	8	4/0	532 19x28	0.150	0.295	3.39	86.1	9909	14746

ELECTRICAL AND MECHANICAL PARAMETERS

Power-Grounding Conductor Size	Power Conductor Resistance at 20°C	Grounding Conductor Resistance at 20°C	Ground Check Conductor Resistance at 20°C	Inductance per unit length	Operating Capacitance per unit length	Permissible Short-Circuit Current ⁽²⁾ (1s)	Ampacity ⁽¹⁾ 40°C Ambient Temp.	Maximum Permissible Tensile Force
AWG or MCM	Ω/1000Ft	Ω/1000Ft	Ω/1000Ft	mH/1000Ft	μF/1000Ft	kA	A	N
4 AWG – 8 AWG	0.274	0.697	0.679	0.129	0.08	3.03	122	950
2 AWG – 6 AWG	0.172	0.436	0.679	0.122	0.09	4.80	159	1500
1 AWG – 5 AWG	0.137	0.349	0.679	0.117	0.09	6.06	184	1900
1/0 AWG – 4 AWG	0.109	0.274	0.679	0.113	0.10	7.65	211	2400
2/0 AWG – 3 AWG	0.0868	0.227	0.679	0.107	0.11	9.64	243	3000
3/0 AWG – 2 AWG	0.0688	0.172	0.679	0.106	0.11	12.15	279	3800
4/0 AWG – 1 AWG	0.0546	0.137	0.679	0.101	0.13	15.30	321	4800
250 MCM – 1/0 AWG	0.0466	0.109	0.436	0.094	0.16	18.16	355	5800
350 MCM – 2/0 AWG	0.0333	0.0868	0.436	0.090	0.18	25.31	435	7900
500 MCM – 4/0 AWG	0.0233	0.0546	0.436	0.086	0.21	36.18	536	11400

(1) Ampacity- Free air measured; Based on continuous duty at 90°C conductor temperature (2) Short-circuit current (1s) – Based on conductor temperature from 90°C up to 250°C

STANDARD PRINT LEGEND:

TF CABLE 8000V (SIZE) TYPE SHD-GC FT1 FT5 (-50C) +90C P-07-KA060012-MSHA



1160 Pierson Drive, Suite 102 Batavia, IL 60510 | tel: 630-406-9000 fax: 630-406-6574
e-mail: sales@tfcable.com | http://www.tfcable.com