



Connecting globally

PORTABLE POWER CABLE

FLEXTREME^{TC}

FLEXTREME^{TC} is a new line of power and control cables. These products are characterized by high flexibility and durability. Enhanced performance properties have been achieved through the use of specially developed rubber formulations which have been used for both the XHHW-2 (EPR) insulation as well as on the sheath (CPE). The obtained flexibility guarantees the contractor exceptionally easy cable assembly.



Power

- Insulated power conductors
- Unshielded ICEA Method 4

Control

- Insulated ground conductor
- Unshielded Method 1, Table E-1 or E-2 Color Code



Unique features

Excellent flame resistant: FT4 UL 1685. Excellent thermal properties: maximum conductor temperature: 90°C. Excellent physical, thermal and electrical properties. Excellent resistant to a low temperature: -40°C. Meets cold bend test at -25°C. Oil resistant: UL 1277. Ozone resistant: EN 60811-403, method A. Moisture, water, weather, sunlight resistant. Excellent resistance to crush, compression cuts and heat deformation.

Proven functional solution

Insulation type XHHW-2. Flame retardant (FT4), lead free easy to strip. CPE jacket lead free flame retardant does not exhibit falling hot droplets.

555 Remington Blvd. Suite A. Bolingbrook, IL 60440
phone: (630) 406-9000 or email: sales@tfcable.com

All information contained in this document, including the tables and drawings, are provided for information only and not a commercial offer; nor may it constitute the basis for pursuing any claim against TELE-FONIKA Kable S.A.