



PUMP CABLE W/GRD

2000 V

Based on: ASTM B3, UL 44, ICEA S-75-381

Flat Pump Power Cables

APPLICATIONS

- Heavy-duty flexible for supplying power to pumps
- Other industrial applications

CONSTRUCTION

Conductors	Soft drawn flexible stranded bare copper wires
Separator	A suitable tape separator between the conductor and insulation
Insulation	Ethylene-propylene rubber (EPR)
Circuit identification	Black, red, yellow
Grounding conductor	Soft drawn flexible stranded bare copper wires Insulation color: green-yellow
Assembly	Three power and grounding conductor shall be laid parallel. Single faced rubber filled binder tape applied over each conductor
Jacket	Black heavy duty, CPE thermosetting compound

Features

Excellent flexibility	Oil and heat resistant
Water, ozone, sun, weather and flame resistant	Suitable for shallow water immersion
Temperature range -40°C to +90°C	Ink jet or indeed printed for easy identification



PUMP CABLE W/GRD

Approvals

UL:	E193954
MSHA:	P-07-KA060001
Standard length cable packing	1000ft on drums. Other forms of packing and delivery are available on request

Part number	Conductor size	Power conductor stranding	Nominal Insulation Thickness		Approx. Outside dimensions		Approx. Weight		Ampacity(1)
			Inches	mm	Inches	mm	lbs/1000ft	kg/km	
PC6-3WG-FLT	3x6 + 8	259 x 0.01	0.07	1.78	0.60 x 1.72	15.3 x 43.6	810	1205	75
PC4-3WG-FLT	3x4 + 6	412 x 0.01	0.07	1.78	0.67 x 1.87	17.0 x 47.4	1090	1622	95
PC2-3WG-FLT	3x2 + 5	259 x 0.0159	0.07	1.78	0.72 x 2.08	18.2 x 52.8	1425	2121	130
PC1-3WG-FLT	3x1 + 4	332 x 0.0159	0.09	2.29	0.82 x 2.41	20.8 x 61.2	1865	2776	145
PC1/0-3WG-FLT	3x1/0 + 3	414 x 0.0159	0.09	2.29	0.87 x 2.58	22.1 x 65.5	2216	3298	170
PC2/0-3WG-FLT	3x2/0 + 2	522 x 0.0159	0.09	2.29	0.85 x 2.70	21.5 x 68.5	2640	3928	195
PC4/0-3WG-FLT	3x4/0 + 1/0	829 x 0.0159	0.09	2.29	1.14 x 3.37	29.0 x 85.6	4034	6003	260
PC250-3WG-FLT	3x250 + 2/0	973 x 0.0159	0.105	2.67	1.33 x 3.89	33.9 x 98.8	5110	7604	290
PC350-3WG-FLT	3x350 + 3/0	1361 x 0.0159	0.105	2.67	1.41 x 4.28	35.8 x 108.7	6392	9512	350
PC500-3WG-FLT	3x500 + 250	1921 x 0.0159	0.105	2.67	1.56 x 4.89	39.7 x 124.1	8487	12630	430

(1) Ampacities based on 90°C Conductor and 30°C Ambient temperature per table 310.16 of the National Electrical Code®

Standard Print Legend

TF CABLE (SIZE) / 3C W/GRD SUBMERSIBLE PUMP CABLE EPR/CPE (VOLTAGE) (UL) E193954 P-07-KA060001-MSHA

The information contained in this document, including the tables and drawings, are provided for illustrative purposes only and not a commercial offer; nor may it constitute the basis for pursuing any claim against TELE-FONIKA KABLE SA. The suitability of any product including properties, should be made by a qualified person; having already gained the appropriate permissions and documentation, to ensure compliance with any applicable law or regulation.