



SHD-GC

2000 V

CSA C22.2 No. 96-17

Round portable power cable. Mining grade

APPLICATIONS

- Use on AC off track equipment such as long wall miners loaders, drills, shovels, conveyors, pumps and mobile equipment requiring grounding conductors and a ground check conductor and metallic shielding overall
- Other industrial, mining applications

CONSTRUCTION

Conductors	Soft drawn flexible stranded tinned copper wires
Separator	Polyester tape
Insulation	Ethylene-propylene rubber (EPR)
Insulation shield	Non-conducting bedding tape + composite tinned copper/ polyamide braid. Covering minimum 60%
Circuit identification	The polyamide in the shielding braid is colored black, black, red
Grounding	Soft drawn flexible stranded tinned copper wires
Ground check	Sizes 14AWG and smaller: Yellow TPE-E insulated soft drawn flexible stranded tinned copper wires
	Sizes 12AWG and larger: Yellow PP insulated soft drawn flexible stranded tinned copper wires
Assembly	Three power, ground check and two non-insulated grounding conductors cabled together to form a round cable core
Separator	Polyamide open braid applied overall
Outer jacket	Extra heavy duty, high torsion resistant, integral-filled, reinforced poly-chloroprene (CR) thermosetting jacket
Color of outer jacket	Black
Minimum bending radius	Six times overall diameter of the cable



SHD-GC

Features

Excellent flexibility	Excellent impact and abrasion resistant
Highly ozone, sun, weather and flame resistant	Oil and heat resistant
Rated and flexible at -40°C	Indent printed for easy identification

Approvals

CSA:	1523058 (LR 103932)
MSHA:	P-07-KA060012-2 (for sizes 14AWG-500MCM)
Standard length cable packing	1000ft on drums. Other forms of packing and delivery are available on request

Selection Data

Part Number	Cond. Size	Cond. Strand	Cond. Size		Nominal Insulation Thickness		Nominal Jacket Thickness		Approx. O.D.		Approx. Weight		Maximum Tensile Force
	AWG/MCM	No.	GRD	GC	Inches	mm	Inches	mm	Inches	mm	Lbs./1kft.	kg/km	N
SHDGC2KV14-3CSA	14	49	14	14	0.070	1.78	0.125	3.18	0.91	23.0	487	725	94
SHDGC2KV12-3CSA	12	49	12	14	0.070	1.78	0.125	3.18	0.91	23.0	515	766	148
SHDGC2KV10-3CSA	10	49	12	12	0.070	1.78	0.125	3.18	0.97	24.6	593	882	238
SHDGC2KV8-3CSA	8	133	10	10	0.070	1.78	0.140	3.56	1.05	26.6	745	1109	380
SHDGC2KV6-3CSA	6	133	10	10	0.070	1.78	0.155	3.94	1.22	31.0	1011	1504	600
SHDGC2KV4-3CSA	4	259	9	10	0.070	1.78	0.155	3.94	1.34	34.1	1297	1930	950
SHDGC2KV2-3CSA	2	259	7	8	0.070	2.03	0.170	4.32	1.52	38.5	1803	2683	1500
SHDGC2KV1-3CSA	1	259	6	8	0.080	2.03	0.190	4.83	1.67	42.4	2151	3201	1900
SHDGC2KV1/0-3CSA	1/0	266	5	8	0.080	2.03	0.190	4.83	1.78	45.2	2542	3782	2400
SHDGC2KV2/0-3CSA	2/0	342	4	8	0.080	2.03	0.205	5.21	1.89	48.1	3020	4494	3000

SHD-GC

Part Number	Cond. Size	Cond. Strand	Cond. Size		Nominal Insulation Thickness		Nominal Jacket Thickness		Approx. O.D.		Approx. Weight		Maximum Tensile Force
			GRD	GC	Inches	mm	Inches	mm	Inches	mm	Lbs./1kft.	kg/km	
	AWG/ MCM	No.	AWG		Inches	mm	Inches	mm	Inches	mm	Lbs./1kft.	kg/km	N
SHDGC2KV3/0-3CSA	3/0	418	3	8	0.080	2.03	0.205	5.21	2.05	52.0	3568	5309	3800
SHDGC2KV4/0-3CSA	4/0	532	2	8	0.080	2.03	0.220	5.59	2.19	55.7	4300	6399	4800
SHDGC2KV250-3CSA	250	627	1	8	0.095	2.41	0.220	5.59	2.38	60.5	5002	7443	5800
SHDGC2KV350-3CSA	350	888	1/0	8	0.095	2.41	0.235	5.97	2.68	68.1	6598	9819	7900
SHDGC2KV500-3CSA	500	1221	3/0	8	0.095	2.41	0.265	6.73	3.05	77.5	8885	13222	11400

Electrical parameters

Power-Grounding Conductor Size	Power Conductor Resistance at 25°C	Grounding Conductor Resistance at 25°C	Ground-check Conductor Resistance at 25°C	Inductance per unit length	Operating Capacitance per unit length	Permissible short-circuit Current (1s) (2)	Ampacity(1) 40°C Ambient Temp
MCM	Ω/1000Ft	Ω/1000Ft	Ω/1000Ft	mH/1000Ft	μF/1000Ft	kA	A
6 AWG	0.436	1.08	1.08	0.118	0.09	1.90	93
4 AWG	0.274	0.857	1.08	0.107	0.11	3.03	122
2 AWG	0.172	0.539	0.679	0.101	0.13	4.80	159
1 AWG	0.137	0.436	0.679	0.100	0.13	6.06	184
1/0 AWG	0.109	0.346	0.679	0.097	0.14	7.65	211
2/0 AWG	0.0868	0.274	0.679	0.092	0.16	9.64	243
3/0 AWG	0.0688	0.217	0.679	0.091	0.17	12.15	279
4/0 AWG	0.0546	0.172	0.679	0.088	0.19	15.30	321
250 MCM	0.0466	0.137	0.679	0.084	0.21	18.16	355
350 MCM	0.0333	0.109	0.679	0.081	0.24	25.31	435
500 MCM	0.0233	0.0688	0.679	0.078	0.28	36.18	536

(1) Ampacity – Based on continuous duty at 90°C conductor temperature

(2) Short-circuit current (1s) – Based on conductor temperature from 90°C up to 250°C

SHD-GC

Special Factory Options:

Jacket:	Other colors available
Jacket:	TPU jacket available

Standard Print Legend

TF CABLE (VOLTAGE) 3/C (SIZE) TYPE SHD-GC CSA LR 103932 FT1 FT5 (-40°C) +90°C P-07-KA060012-2-MSHA

The information contained in this document, including the tables and drawings, are provided for illustrative purposes only and not a commercial offer; nor may it constitute the basis for pursuing any claim against TELE-FONIKA KABLE SA. The suitability of any product including properties, should be made by a qualified person; having already gained the appropriate permissions and documentation, to ensure compliance with any applicable law or regulation.