



SHD-GC

5kV



CSA C22.2 No.96-17

Round portable power cable Mining grade

APPLICATIONS

Use on AC off track equipment such as long wall miners loaders, drills, shovels, conveyors, pumps and mobile equipment requiring grounding conductors and a ground check conductor and metallic shielding overall. Other industrial, mining applications

CONSTRUCTION

Conductors	Soft drawn flexible stranded tinned copper wires
Conductor shield	Semi-conducting layer over the conductor
Insulation	Ethylene-propylene rubber (EPR)
Insulation shield	None-conducting bedding tape + composite tinned copper/polyamide braid. Covering minimum 60%.
Circuit identification	The polyamide in the shielding braid is coloured black, blue, red
Grounding	Soft drawn flexible stranded tinned copper wires
Ground check	Yellow PP insulated soft drawn flexible stranded tinned copper wires
Assembly	Three power, ground check and two non-insulated grounding conductors cabled together to form a round cable core
Separator	A single faced rubber filled binder tape applied over core
Outer jacket	Extra heavy duty, high torsion resistant, integral-filled, reinforced poly-chloroprene (CR) thermosetting jacket
Colour of outer jacket	Black or color can be provided
Minimum bending radius	Six times overall diameter of the cable



Features

Excellent flexibility. Highly ozone, sun, weather and flame resistant. Rated and flexible at -40°C. Excellent impact and abrasion resistant. Oil and heat resistant. Indent printed for easy identification.

Approvals

CSA: 1523058 (LR 103932), FT 1, FT-5. MSHA: P-07-KA060012-2 (for sizes 6AWG-500MCM)

Standard length cable packing

1000ft on drums. Other forms of packing and delivery are available on request

Selection Data

Part Number	Cond. Size	Cond. Strand	Cond. Size		Nominal Insulation Thickness		Nominal Jacket Thickness		Approx. O.D.		Approx. Weight		Max. Tensile Force
	AWG/MCM	No. of wires	AWG	GRD	Inches	mm	Inches	mm	Inches	mm	Lbs./1000ft.	kg/km	N
SHDGC5KV6-3 CSA	6	133	10	8	0.110	2.79	0.185	4.70	1.50	38.1	1365	2031	600
SHDGC5KV4-3 CSA	4	259	9	8	0.110	2.79	0.185	4.70	1.59	40.4	1656	2465	950
SHDGC5KV2-3 CSA	2	259	7	8	0.110	2.79	0.205	5.21	1.79	45.5	2429	3614	1500
SHDGC5KV1-3 CSA	1	259	6	8	0.110	2.79	0.205	5.21	1.85	47.1	2448	3643	1900
SHDGC5KV1/0-3 CSA	1/0	266	5	8	0.110	2.79	0.220	5.59	1.96	49.9	2838	4225	2400
SHDGC5KV2/0-3 CSA	2/0	342	4	8	0.110	2.79	0.220	5.59	2.07	52.6	3353	4989	3000
SHDGC5KV3/0-3 CSA	3/0	418	3	8	0.110	2.79	0.235	5.97	2.23	56.6	3951	5880	3800
SHDGC5KV4/0-3 CSA	4/0	532	2	8	0.110	2.79	0.235	5.97	2.37	60.2	4693	6983	4800
SHDGC5KV250-3 CSA	250	627	1	8	0.120	3.05	0.250	6.35	2.57	65.3	5427	8076	5800
SHDGC5KV350-3 CSA	350	888	1/0	8	0.120	3.05	0.265	6.73	2.82	71.7	6960	10357	7900
SHDGC5KV500-3 CSA	500	1221	3/0	8	0.120	3.05	0.280	7.11	3.18	80.7	9255	13772	11400

Electrical parameters

Power-Grounding Conductor Size	Power Conductor Resistance at 25°C	Grounding Conductor Resistance at 25°C	Ground-check Conductor Resistance at 25°C	Inductance per unit length	Operating Capacitance per unit length	Permissible short-circuit Current (1s) (2)	Ampacity(1) 40°C Ambient Temp
AWG or MCM	Ω/1000Ft	Ω/1000Ft	Ω/1000Ft	mH/1000Ft	μF/1000Ft	kA	A
6 AWG	0,436	0,857	0,679	0,132	0,08	1,90	93
4 AWG	0,274	0,857	0,679	0,119	0,09	3,03	122
2 AWG	0,172	0,539	0,679	0,112	0,10	4,80	159
1 AWG	0,137	0,436	0,679	0,108	0,11	6,06	184
1/0 AWG	0,109	0,346	0,679	0,105	0,12	7,65	211
2/0 AWG	0,0868	0,274	0,679	0,099	0,14	9,64	243
3/0 AWG	0,0688	0,217	0,679	0,098	0,14	12,15	279
4/0 AWG	0,0546	0,172	0,679	0,094	0,16	15,30	321
250 MCM	0,0466	0,137	0,679	0,089	0,18	18,16	355
350 MCM	0,0333	0,109	0,679	0,085	0,21	25,31	435
500 MCM	0,0233	0,0688	0,679	0,082	0,24	36,18	536

(1) Ampacity –Based on continuous duty at 90°C conductor temperature

(2) Short-circuit current (1s) – Based on conductor temperature from 90°C up to 250°C



Standard print legend:

TF CABLE 5000V 3/C (SIZE) TYPE SHD-GC CSA LR 103932 100% FT1 FT5 (-40°C) +90°C P-07-KA060012-2-MSHA

Special factory option

Jacket	Other colors available
Jacket	TPU jacket available