



SOOW/H07RN-F

750 V

UL 62 and EN 50525-2-21

Portable cord and control cable, Integral version

APPLICATIONS

- Industrial and processing equipment, cranes and hoists, track systems, tools, construction equipment, motors and associated machinery, garage portable lights, battery charger and equipment exposed to oils, solvents, flame, moisture and other electrical equipment
- Other industrial applications

CONSTRUCTION

Conductors	Flexible stranded bare copper in accordance with UL 62, IEC 60228
Separator	Paper tape from 9AWG and above
Insulation	EPR thermosetting compound
Color code	3/C Green/Yellow, Blue, Brown 4/C Green/Yellow, Brown, Black, Grey 5/C Green/Yellow, Blue, Brown, Black, Grey
Cabling	Insulated conductors are assembled round without fillers
Separator	Polyester tape
Outer jacket	CPE thermosetting compound
Color of outer jacket	Black. Other colors available on request



Features

Excellent flexibility, resistance to oil, solvents, ozone, weather, sunlight and water.

UV, sunlight, ozone, oil resistant

Temperature range -40°C to +90°C

Ink jet printed for easy identification

SOOW/H07RN-F

Approvals

(UL) & CUL:	E123366
MSHA:	P-7K-254013
CSA:	1534535 (LL 103932)
BBJ:	<HAR>
Standard length cable packing	250, 500 or 1000 ft on drums. Other forms of packing and delivery are available on request

Part Number	Size	No of Cond.	Conductor Strand	Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal Overall diameter	Min Overall diameter	Max Overall diameter	Weight	Ampacity at 30°C in air ¹⁾					
	mm ² (AWG)	N	Inch.	mm	Inch.	mm	Inch.	mm	Inch.	mm	Inch.	mm	lbs /1000ft	A	
SOOW/H07RN-F 17AWG-2		2	32/0.2	0.032	0.81	0.063	1.60	0.363	9.2	0.35	8.89	0.39	9.91	75	10
SOOW/H07RN-F 17AWG-3	1.04mm ² (17 AWG)	3	32/0.2	0.032	0.81	0.063	1.60	0.386	9.8	0.374	9.50	0.402	10.20	84	10
SOOW/H07RN-F 17AWG-4		4	32/0.2	0.032	0.81	0.063	1.60	0.412	10.5	0.400	10.16	0.445	11.3	99	7
SOOW/H07RN-F 17AWG-5		5	32/0.2	0.032	0.81	0.080	2.03	0.479	12.2	0.465	11.81	0.516	13.1	139	5.6
SOOW/H07RN-F 13AWG-4	2.63mm ² (13 AWG)	4	52/0.25	0.047	1.19	0.085	2.16	0.594	15.1	0.575	14.6	0.61	15.5	220	15
SOOW/H07RN-F 11AWG-3		3	57/0.3	0.047	1.19	0.095	2.41	0.628	15.9	0.610	15.5	0.638	16.2	253	25
SOOW/H07RN-F 11AWG-4	4.17 mm ² (11 AWG)	4	57/0.3	0.047	1.19	0.10	2.54	0.689	17.5	0.660	16.7	0.705	17.9	306	20
SOOW/H07RN-F 11AWG-5		5	57/0.3	0.047	1.19	0.10	2.54	0.748	19.0	0.72	18.3	0.783	19.9	368	16

SOOW/H07RN-F

Part Number	Size	No of Cond.	Conductor Strand	Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal Overall diameter	Min Overall diameter	Max Overall diameter	Weight	Ampacity at 30°C in air ¹⁾
	mm ² (AWG)	N	Inch. mm	Inch. mm	Inch. mm	Inch. mm	Inch. mm	Inch. mm	lbs /1000ft	A
SOOW/H07RN-F 9AWG-3		3	91/0.3	0.047 1.19	0.10 0.10	2.54 0.693	17.6 0.670	17.0 0.709	18 327	30
SOOW/H07RN-F 9AWG-4	6.63 mm ² (9 AWG)	4	91/0.3	0.047 1.19	0.10 0.10	2.54 0.752	19.1 0.725	18.4 0.787	20 394	25
SOOW/H07RN-F 9AWG-5		5	91/0.3	0.047 1.19	0.106 0.106	2.70 0.827	21.0 0.795	20.2 0.874	22.2 479	20
SOOW/H07RN-F 7AWG-3		3	82/0.4	0.062 1.57	0.135 0.135	3.43 0.917	23.3 0.909	23.0 0.953	24.2 572	40
SOOW/H07RN-F 7AWG-4	10.6 mm ² (7 AWG)	4	82/0.4	0.062 1.57	0.140 0.140	3.56 1.004	25.5 0.988	25.1 1.043	26.5 705	35
SOOW/H07RN-F 7AWG-5		5	82/0.4	0.062 1.57	0.142 0.142	3.60 1.091	27.7 1.080	27.4 1.146	29.1 841	28
SOOW/H07RN-F 5AWG-5	16.8 mm ² (5AWG)	5	133/0.4	0.062 1.57	0.154 0.154	3.9 1.270	32.3 1.252	31.8 1.311	33.3 1176	36

1) Ampacity - Based on continuous duty at 90°C conductor temperature
 Ampacity values shown are for current carrying conductors. A grounding conductor, or one which carries only the unbalanced current from other conductors, is not counted in determining current carrying capacity

Standard Print Legend

17 AWG ¹⁾:

TF KABLE 3 17AWG (1,0MM²)/3C (UL) SOOW 600V 90°C E123366 c(UL) SOOW 600V 90°C FT2 --- BBJ < HAR > H07RN-F ROHS

1*) For 17AWG size "CE" mark is printed on the reel tags

Above 17 AWG:

TF KABLE 3 9AWG (6,0MM²)/5C (UL) SOOW 600V 90°C E123366 c(UL) SOOW 600V 90°C FT2 --- BBJ <HAR> H07RN-F CE ROHS

The information contained in this document, including the tables and drawings, are provided for illustrative purposes only and not a commercial offer; nor may it constitute the basis for pursuing any claim against TELE-FONIKA KABLE SA. The suitability of any product including properties, should be made by a qualified person; having already gained the appropriate permissions and documentation, to ensure compliance with any applicable law or regulation.